

+44 (0)161 928 6221 info@hydratron.co.uk

TECHNICAL DATA SHEET

PRODUCT	GPU-GBD118-L**/options
SERIES	GPU- Single Stage Double Acting Air operated, high flow gas booster compressors offer a flexible and efficient source for delivering high pressure gases.



FEATURES


- Infinitely variable output pressure and flow
- Will hold static pressure without generating heat or consuming power
- Standard models are suitable for various gases
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

PERFORMANCE DATA

Max Rated Output Pressure	14,200psi (980bar)
Displacement Per Cycle	4.5 in ³ (73.7cc)
Max Flow	20.4 scfm (577 NI/min)
Max Air Supply Pressure	100psi (7bar)
Ratio	15:1
Air Consumption	120 scfm (3,400 NI/min)
Supply Pressure to Achieve Max Output Pressure	2,400psi (165bar)
Actual Output Pressure (Stall Condition)	118 x (Air drive pressure) + (Supply pressure)

SEAL MATERIAL

Main Seals	MoS2
Check Valve Seals	Viton









Pag. 2 of 3

CONSTRUCTION


Frame	Stainless Steel
Air Motor	Anodised Aluminium / Nitrile (Buna-N) Seals
Gas Cylinder	17-4PH
Piston	17-4PH + Chrome Finish
Check Valves	Stainless Steel
Pilot Air Valves	Brass / Stainless Steel Internals / Nitrile (Buna-N) Seals / Stainless Steel Silencer
L1** (standard)	Brass / Copper Gas Inlet, Air Inlet and Plated Steel Silencer
L2** (optional)	Stainless Steel Gas Inlet, Air Inlet and Silencer

CONNECTIONS

Gas Inlet	1/4" NPT(F)
Gas Outlet	1/4" HP(F)
Air Inlet	3/4" BSPP(F)
Net Weight	100kg (220lb)

COMMON OPTIONS (BUT NOT LIMITED TO)

ATEX (94/9/EC) II 2GD c T5
Panel mount digital stroke counter (non ATEX)
Panel mount pneumatic stroke counter
Isolation valve
Inlet gas gauge
Mild steel painted frame (Painted Blue) + Stainless steel tank (if applicable to the unit)
Single pen chart recorder complete with recorder isolation valve
Relief valve
Fitted with wheels
Gauge protection guard







GENERAL LAYOUT DRAWING

Model: GPU-GBD118

