

TECHNICAL DATA SHEET

PRODUCT	HPU-HP10-100-N*/options		
SERIES	HPU-HP		
	Hand operated hydraulic pumps for pressure testing purposes, suitable for either oil or water services.		

FEATURES

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power.
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

PERFORMANCE DATA		
Max Rated Output Pressure	10,000psi (690bar)	
Output Per Cycle	LP pump 3 in³ (49 cc/ml) HP pump 0.3 in³ (5 cc/ml)	
Tank Capacity	1 Gallon (4.5 L)	
SEAL OPTIONS (N*)		
N* (standard)	Nitrile (Buna-N) Main Seal and Check Valve Seals	
EPDM	EPDM Main Seal and Check Valve Seals	
CONSTRUCTION		
Frame and Tank	Stainless Steel	
Body	Stainless Steel	
Piston	Stainless Steel + Chrome Finish	

Stainless Steel (Seals as per Selected Seal Option)



Check Valves

Model: HPU-HP10-100-N



Pag. 2 of 2

Handle	Stainless Steel Handle – Rubber Grip (23 1/2" 600mm LG)
--------	---

CONNECTIONS

Hydraulic Outlet	3/8" NPT(F)
Net Weight	26kg (57lb)

COMMON OPTIONS (BUT NOT LIMITED TO)

/ B	Recorder Connection
/ 2	Isolation valve

GENERAL LAYOUT DRAWING

