

TECHNICAL DATA SHEET

PRODUCT	HPU-HP150-N*/options	
SERIES	HPU-HP Hand operated hydraulic pumps for pressure testing purposes, suitable for either oil or water services.	

FEATURES

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power.
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

PFR		# A b i		T A

Max Rated Output Pressure	15,000psi (1,034bar)
Output Per Cycle	0.17 in ³ (3cc/ml)
Tank Capacity	1 Gallon (4.5L)

SEAL OPTIONS (N*)

N* (standard)	Nitrile (Buna-N) Main Seal and Check Valve Seals
EPDM	EPDM Main Seal and Check Valve Seals

\sim	TPM	 OTI	\sim 1 \sim 1
	\sim		

Frame and Tank	Stainless Steel
Body	Stainless Steel
Piston	Stainless Steel + Chrome Finish
Check Valves	Stainless Steel (Seals as per Selected Seal Option)





Pag. 2 of 2

CONNECTIONS	
Hydraulic Outlet	1/4" HP(F)
Net Weight	20kg (44lb)

COMMON OPTIONS (BUT NOT LIMITED TO)

/ B	Recorder Connection
/2	Isolation valve

GENERAL LAYOUT DRAWING

Model: **HPU-HP150-N**

