

TECHNICAL DATA SHEET

PRODUCT	HPU-HP250-N*/options	
SERIES	HPU-HP	
	Hand operated hydraulic pumps for pressure testing purposes, suitable for either oil or water services.	

FEATURES

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power.
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

PERFORMANCE DATA

SEAL OPTIONS (N*)

TERT ORMANGE DATA		
Max Rated Output Pressure	25,000psi (1,724bar)	
Output Per Cycle	0.12 in³ (2cc/ml)	
Tank Capacity	1 Gallon (4.5L)	

N* (standard)	Nitrile (Buna-N) Main Seal and Check Valve Seals
EPDM	EPDM Main Seal and Check Valve Seals

CONSTRUCTION	
Frame and Tank	Stainless Steel
Body	Stainless Steel
Piston	Stainless Steel + Chrome Finish
Check Valves	Stainless Steel (Seals as per Selected Seal Option)
Handle	Stainless Steel Handle – Rubber Grip (23 1/2" 600mm LG)



CO	AIA	ECT	VIC
LU		IECT	c_{V}

Hydraulic Outlet	1/4" HP(F)
Net Weight	9kg (20lb)

COMMON OPTIONS (BUT NOT LIMITED TO)

/ B	Recorder Connection
/ 2	Isolation valve

GENERAL LAYOUT DRAWING

Model: HPU-HP250-N

