

TECHNICAL DATA SHEET

PRODUCT	HPU-HP30-N*/options	
SERIES	HPU-HP	
	Hand operated hydraulic pumps for pressure testing purposes, suitable for either oil or water services.	

FEATURES

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power.
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

PERFORMANCE DATA

SEAL OPTIONS (N*)

Max Rated Output Pressure	3,000psi (207bar)
Output Per Cycle	1 in³ (16.3cc)
Tank Capacity	1 Gallon (4.5L)

. ,	
N* (standard)	Nitrile (Buna-N) Main Seal and Check Valve Seals
EPDM	EPDM Main Seal and Check Valve Seals

CONSTRUCTION		
Frame and Tank	Stainless Steel	
Body	Stainless Steel	
Piston	Stainless Steel + Chrome Finish	
Check Valves	Stainless Steel (Seals as per Selected Seal Option)	
Handle	Stainless Steel Handle – Rubber Grip (23 1/2" 600mm LG)	

Model: HPU-HP30-N



00	RIBIE	CT		10
CU	NNE	: G I	UN	

Hydraulic Outlet	3/8" NPT(F)
Net Weight	20kg (44lb)

COMMON OPTIONS (BUT NOT LIMITED TO)

/ B	Recorder Connection
/ 2	Isolation valve

GENERAL LAYOUT DRAWING



