


## TECHNICAL DATA SHEET

PRODUCT	<b>PU-GBS186-L**/options</b>	
SERIES	<b>Single Acting</b> Air operated, high flow gas booster compressors offer a flexible and efficient source for delivering high pressure gases.	

### FEATURES

- Infinitely variable output pressure and flow
- Will hold static pressure without generating heat or consuming power
- Standard models are suitable for various gases
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

### PERFORMANCE DATA

Max Rated Output Pressure	18,600psi (1,282bar)
Displacement Per Cycle	0.49 in <sup>3</sup> (8cc)
Max Flow	2.76 scfm (78 NI/min)
Max Air Supply Pressure	100psi (7bar)
Ratio	12 : 1
Air Consumption	56 scfm (1,586 NI/min)
Supply Pressure to Achieve Max Output Pressure	1,550psi (107bar)
Actual Output Pressure (Stall Condition)	186 x (Air drive pressure)

### SEAL MATERIAL

Main Seals	MoS2
Check Valve Seals	Viton

### CONSTRUCTION

Air Motor	Anodised Aluminium / Wound Composite / Nitrile (Buna-N) Seals
Gas Cylinder	17-4PH
Piston	17-4PH + Chrome Finish
Check Valves	Stainless Steel
L1** (standard)	Copper / Brass, Pipework / Fittings & Plated Steel Silencer
L2** (optional)	Stainless Steel Pipework, Fittings & Silencer

### CONNECTIONS

Gas Inlet	3/8" NPT(F)
Gas Outlet	1/4" HP(F)
Net Weight	16kg (35lb)

### COMMON OPTIONS (BUT NOT LIMITED TO)

/ A	ATEX - Zone 1 Category II
/ F	Panel mount digital stroke counter (non ATEX)
/ G	Panel mount pneumatic stroke counter

GENERAL LAYOUT DRAWING

Model: PU-GBS186

