

TECHNICAL DATA SHEET

PRODUCT	PU-HP10-N*/options		
SERIES	НР		
	Hand operated hydraulic pumps for pressure testing purposes, suitable for either oil or water services.		

FEATURES

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power.
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

PERFORMANCE DATA		
Max Rated Output Pressure	1,000psi (69bar)	
Output Per Cycle	3 in³ (49cc/ml)	
SEAL OPTIONS (N*)		
N* (standard)	Nitrile (Buna-N) Main Seal and Check Valve Seals	
EPDM	EPDM Main Seal and Check Valve Seals	
CONSTRUCTION		
Body	Stainless Steel	
Piston	Stainless Steel	
Check Valves	Stainless Steel (Seals as per Selected Seal Option)	
Handle	Stainless Steel Handle – Rubber Grip (23 1/2" 600mm LG)	

Model: PU-HP10-N



Pag. 2 of 2

CONNECTIONS		
Hydraulic Inlet	1/4" NPT(F)	
Hydraulic Outlet	1/4" NPT(F)	
Net Weight	9kg (20lb)	

COMMON OPTIONS (BUT NOT LIMITED TO)

/1	Pressure release valve
/ 2	Isolation valve

GENERAL LAYOUT DRAWING



