

+44 (0) 161 928 6221 | info@hydratron.co.uk

-

TECHNICAL DATA SHEET

PRODUCT	PU-HP100-N*/options		
SERIES	HP Hand operated hydraulic pumps for pressure testing purposes, suitable for either oil or water services.		
FEATURE	S		

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power.
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing Robust construction

PERFORMANCE DATA

Max Rated Output Pressure	10,000psi (690bar)
Max Nated Output I Tessure	10,000psi (090bai)
Output Per Cycle	0.30 in ³ (5cc/ml)

SEAL OPTIONS (N*)		
N* (standard)	Nitrile (Buna-N) Main Seal and Check Valve Seals	
EPDM	EPDM Main Seal and Check Valve Seals	

CONSTRUCTION

Body	Stainless Steel
Piston	Stainless Steel + Chrome Finish
Check Valves	Stainless Steel (Seals as per Selected Seal Option)
Handle	Stainless Steel Handle – Rubber Grip (23 1/2" 600mm LG)

CONNECTIONS

A THREE60 ENERGY COMPANY





Technical Data Sheet

Pag. 2 of 2

Hydraulic Inlet	1/4" NPT(F)
Hydraulic Outlet	1/4" NPT(F)
Net Weight	9kg (20lb)

COMMON OPTIONS (BUT NOT LIMITED TO)

/ 1	Pressure release valve
/2	Isolation valve

GENERAL LAYOUT DRAWING

Model: PU-HP100-N



