

+44 (0) 161 928 6221 | info@hydratron.co.uk

1.

# **TECHNICAL DATA SHEET**

PRODUCT	PU-HP30-N*/options	
SERIES	<b>HP</b> Hand operated hydraulic pumps for pressure testing purposes, suitable for either oil or water services.	

## FEATURES

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power.
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing Robust construction

### PERFORMANCE DATA

Max Rated Output Pressure	3,000psi (207bar)
Output Per Cycle	1 in <sup>3</sup> (16.3cc)

SEAL OPTIONS (N*)		
N* (standard)	Nitrile (Buna-N) Main Seal and Check Valve Seals	
EPDM	EPDM Main Seal and Check Valve Seals	

#### CONSTRUCTION

Body	Stainless Steel
Piston	Stainless Steel + Chrome Finish
Check Valves	Stainless Steel (Seals as per Selected Seal Option)
Handle	Stainless Steel Handle – Rubber Grip (23 1/2" 600mm LG)





### **Technical Data Sheet**

Pag. 2 of 2

CONNECTIONS		
Hydraulic Inlet	1/4" NPT(F)	
Hydraulic Outlet	1/4" NPT(F)	
Net Weight	9kg (20lb)	

## COMMON OPTIONS (BUT NOT LIMITED TO)

/ 1	Pressure release valve
/ 2	Isolation valve

#### **GENERAL LAYOUT DRAWING**

#### Model: PU-HP30-N



