

TECHNICAL DATA SHEET

PRODUCT	Rice Petrol Driven Hydrostatic Test Pump
MODELS	TR-2, TR-6, TRH-8, TRH-10
SERIES	TRIPLEX HIGH PRESSURE



The TR-Series are large volume high pressure hydrostatic test pumps designed for testing boilers, vessels, process piping, steam and gas lines. The triplex ceramic plunger pump has an inner oil bath, ensuring long life and increased stability. Their high flow characteristics for pumps in this pressure range will speed test as it quickly removes air from the test environment. There are no external moving parts for operator safety and reduced liability risks. Virtually indestructible, the TR-Series is enclosed in a rugged roll cage of welded heavy gauge steel.

RI-10 - Wheel and handle kit available (except for TRE-6F which comes complete with castors as standard).

FEATURES

- Automatic Pressure Regulator with Inlet Bypass
- Rugged Roll Cage & Heavy Gauge Steel Base, Protects Pump from Damage
- High Pressure Ball Valve to Isolate Pressure
- · Stainless Steel Liquid-Filled Gauge Ensures Accurate Readings, with Less Flutter

SPECIFICATIONS				
PUMP	TR-2	TR-6	TRH-8	TRH-10
PSI	2000	3000	3600	5000
BAR	138	207	248	345
GPM (LPM)	2.2 (10)	3.3 (15)	3.3 (15)	3.3 (15)
Inlet	3/4"	3/4"	3/4"	3/4"
Outlet	3/8"	3/8"	1/2"	3/8"
Motor/ Engine	Briggs 5 ½ HP	Briggs 11 HP	Honda 13 HP	Honda 20 HP
Shipping Dims (cm)	64 x 53 x 43	90 x 64 x 48	90 x 64 x 48	90 x 64 x 53
Shipping Weight	55 kg	67 kg	80.5 kg	114 kg

OPTIONS	
Engines	Petrol (Briggs & Stratton, Honda) or Diesel
	Dual Unloader Valve available

